

JOSF Faker functions incl. examples.

FakerAddressFunctions

Function Name	Description	Example
<code>\${random.address.city()}</code>	Returns a city.	<code>randomCity = \${random.address.city()}</code>
<code>\${random.address.city(locale)}</code>	Returns a city based on locale.	<code>randomCityNL = \${random.address.city(nl)}</code>
<code>\${random.address.cityName()}</code>	Returns a city name.	<code>randomCityName = \${random.address.cityName()}</code>
<code>\${random.address.cityName(locale)}</code>	Returns a city name based on locale.	<code>randomCityNameNL = \${random.address.cityName(nl)}</code>
<code>\${random.address.country()}</code>	Returns a country.	<code>randomCountry = \${random.address.country()}</code>
<code>\${random.address.country(locale)}</code>	Returns a country based on locale.	<code>randomCountryNL = \${random.address.country(nl)}</code>
<code>\${random.address.countryCode()}</code>	Returns a country code.	<code>randomCountryCode = \${random.address.countryCode()}</code>

<code>\${random.address.state()}</code>	Returns a state.	<code>randomState = \${random.address.state()}</code>
<code>\${random.address.state(locale)}</code>	Returns a state based on locale.	<code>randomStateNL = \${random.address.state(nl)}</code>
<code>\${random.address.streetName()}</code>	Returns a street name.	<code>randomStreetName = \${random.address.streetName()}</code>
<code>\${random.address.streetName(locale)}</code>	Returns a street name based on locale.	<code>randomStreetNameNL = \${random.address.streetName(nl)}</code>
<code>\${random.address.zipCode()}</code>	Returns a zip code.	<code>randomZipCode = \${random.address.zipCode()}</code>
<code>\${random.address.zipCode(locale)}</code>	Returns a zip code based on locale.	<code>randomZipCodeNL = \${random.address.zipCode(nl)}</code>

FakerDateFunctions

Function Name	Description	Example
<code>\${random.date.between(from, to, dateFormat)}</code>	Returns a date between given dates in supplied date format.	<code>randomDateBetween = \${random.date.between(2023-01-01,</code>

		2023-12-31, YYYY-MM-dd)} MM-dd)} }
<code>\${random.date.birthdayAdult(dateFormat)}</code>	Returns a date from 18 years and older in supplied date format.	<code>randomBirthdayAdult =</code> <code>\${random.date.birthdayAdult(YYYY-MM-dd)}</code>
<code>\${random.date.birthday(minAge, maxAge, dateFormat)}</code>	Returns a date based on given min and max age in supplied date format.	<code>randomBirthdayFormatted =</code> <code>\${random.date.birthday(10, 30, dd-MM-YYYY)}</code>
<code>\${random.date.future(dateFormat)}</code>	Returns a future date in the coming year in supplied date format.	<code>randomDateFuture =</code> <code>\${random.date.future(YYYY-MM-dd)}</code>
<code>\${random.date.future(atMost, timeUnit, dateFormat)}</code>	Returns a future date in the given at most time unit (DAYS, HOURS, MINUTES, SECONDS) in supplied date format.	<code>randomDateFutureAtMost =</code> <code>\${random.date.future(30, DAYS, YYYY-MM-dd)}</code>
<code>\${random.date.future(atMost, minimum, timeUnit, dateFormat)}</code>	Returns a future date in the given at most time unit (DAYS, HOURS, MINUTES, SECONDS) with a minimum in supplied date format.	<code>randomDateFutureMinMax =</code> <code>\${random.date.future(30, 5, DAYS, YYYY-MM-dd)}</code>
<code>\${random.date.futureRelative(atMost, timeUnit,</code>	Returns a future date in the given at most time unit (DAYS, HOURS, MINUTES,	<code>randomDateFutureRelative =</code> <code>\${random.date.future</code>

<code>referenceDate, dateFormat)}</code>	SECONDS) relative to reference date in supplied date format.	<code>reRelative(30, DAYS, 2023-01-01, YYYY-MM-dd)}</code>
<code>\${random.date.past(dateFormat)}</code>	Returns a past date in the last year in supplied date format.	<code>randomDatePast = \${random.date.past(YYYY-MM-dd)}</code>
<code>\${random.date.past(atMost, timeUnit, dateFormat)}</code>	Returns a past date in the given at most time unit (DAYS, HOURS, MINUTES, SECONDS) in supplied date format.	<code>randomDatePastAtMost = \${random.date.past(30, DAYS, YYYY-MM-dd)}</code>
<code>\${random.date.past(atMost, minimum, timeUnit, dateFormat)}</code>	Returns a past date in the given at most time unit (DAYS, HOURS, MINUTES, SECONDS) with a minimum in supplied date format.	<code>randomDatePastMinimum = \${random.date.past(30, 5, DAYS, YYYY-MM-dd)}</code>
<code>\${random.date.pastRelative(atMost, timeUnit, referenceDate, dateFormat)}</code>	Returns a past date in the given at most time unit (DAYS, HOURS, MINUTES, SECONDS) relative to reference date in supplied date format.	<code>randomDatePastRelative = \${random.date.pastRelative(30, DAYS, 2023-01-01, YYYY-MM-dd)}</code>

FakerFakeValuesFunctions

Function Name	Description	Example
<code>\${random.value.numerify(value)}</code>	Returns a string with '#' characters replaced with random digits (0-9).	<code>numerifyValue = \${random.value.numerify('123456789')}</code>

		<code>erify(###-###-####)}</code>
<code>\${random.value.letterifyLower(value)}</code>	Returns a string with '?' characters replaced with random lowercase letters.	<code>letterifyLowerValue = \${random.value.letterifyLower(???-???-???)}</code>
<code>\${random.value.letterifyUpper(value)}</code>	Returns a string with '?' characters replaced with random uppercase letters.	<code>letterifyUpperValue = \${random.value.letterifyUpper(???-???-???)}</code>
<code>\${random.value.bothifyLower(value)}</code>	Applies both numerify and letterifyLower.	<code>bothifyLowerValue = \${random.value.bothifyLower(###-###-###-###)}</code>
<code>\${random.value.bothifyUpper(value)}</code>	Applies both numerify and letterifyUpper.	<code>bothifyUpperValue = \${random.value.bothifyUpper(###-###-###-###)}</code>
<code>\${random.pickFromList(values)}</code>	Returns a random item from the provided list of values. Each time the function is executed, it will select one value from the given arguments using a pseudo-random generator. The	<code>listNumber = \${random.pickFromList(1,20,50)}</code> <code>listText= \${random.pickFromList</code>

	returned value is trimmed of leading/trailing whitespace.	<code>ist(aap, noot, mies))}</code>
--	---	-------------------------------------

FakerFunFunctions

Function Name	Description	Example
<code>\${random.fun.yodaQuote()}</code>	Returns a Yoda quote.	<code>randomYodaQuote = \${random.fun.yodaQuote()}</code>
<code>\${random.fun.zeldaCharacter()}</code>	Returns a Zelda character.	<code>randomZeldaCharacter = \${random.fun.zeldaCharacter()}</code>
<code>\${random.fun.chuckNorrisFact()}</code>	Returns a Chuck Norris fact.	<code>randomChuckNorrisFact = \${random.fun.chuckNorrisFact()}</code>
<code>\${random.fun.catBreed()}</code>	Returns a Cat breed.	<code>randomCatBreed = \${random.fun.catBreed()}</code>
<code>\${random.fun.catName()}</code>	Returns a Cat name.	<code>randomCatName = \${random.fun.catName()}</code>
<code>\${random.fun.dogBreed()}</code>	Returns a Dog breed.	<code>randomDogBreed = \${random.fun.dogBreed()}</code>
<code>\${random.fun.dogName()}</code>	Returns a Dog name.	<code>randomDogName = \${random.fun.dogName()}</code>

		me() }
<code>\${random.fun.dragonballCharacter() }</code>	Returns a Dragonball character.	randomDragonballCharacter = <code>\${random.fun.dragonballCharacter() }</code>
<code>\${random.fun.name() }</code>	Returns a funny name.	randomFunnyName = <code>\${random.fun.name() }</code>
<code>\${random.fun.gameOfThronesCharacter() }</code>	Returns a Game of Thrones character.	randomGameOfThronesCharacter = <code>\${random.fun.gameOfThronesCharacter() }</code>
<code>\${random.fun.gameOfThronesCity() }</code>	Returns a Game of Thrones city.	randomGameOfThronesCity = <code>\${random.fun.gameOfThronesCity() }</code>
<code>\${random.fun.gameOfThronesDragon() }</code>	Returns a Game of Thrones dragon.	randomGameOfThronesDragon = <code>\${random.fun.gameOfThronesDragon() }</code>
<code>\${random.fun.gameOfThronesHouse() }</code>	Returns a Game of Thrones house.	randomGameOfThronesHouse = <code>\${random.fun.gameOfThronesHouse() }</code>
<code>\${random.fun.gameOfThronesQuote() }</code>	Returns a Game of Thrones quote.	randomGameOfThronesQuote =

		<code>\${random.fun.gameOfThronesQuote()}</code>
<code>\${random.fun.lordOfTheRingsCharacter()}</code>	Returns a Lord of the Rings character.	<code>randomLordOfTheRingsCharacter = \${random.fun.lordOfTheRingsCharacter()}</code>
<code>\${random.fun.lordOfTheRingsLocation()}</code>	Returns a Lord of the Rings location.	<code>randomLordOfTheRingsLocation = \${random.fun.lordOfTheRingsLocation()}</code>
<code>\${random.fun.pokemonLocation()}</code>	Returns a Pokémon location.	<code>randomPokemonLocation = \${random.fun.pokemonLocation()}</code>
<code>\${random.fun.pokemonName()}</code>	Returns a Pokémon name.	<code>randomPokemonName = \${random.fun.pokemonName()}</code>
<code>\${random.fun.superheroName()}</code>	Returns a Superhero name.	<code>randomSuperheroName = \${random.fun.superheroName()}</code>

FakerNameFunctions

Function Name	Description	Example
---------------	-------------	---------

<code>\${random.name.bloodGroup()}</code>	Returns a blood group.	<code>randomBloodGroup = \${random.name.bloodGroup()}</code>
<code>\${random.name.firstName()}</code>	Returns a first name.	<code>randomFirstName = \${random.name.firstName()}</code>
<code>\${random.name.firstName(locale)}</code>	Returns a first name based on locale.	<code>randomFirstNameNL = \${random.name.firstName(nl)}</code>
<code>\${random.name.fullName()}</code>	Returns a full name.	<code>randomFullName = \${random.name.fullName()}</code>
<code>\${random.name.fullName(locale)}</code>	Returns a full name based on locale.	<code>randomFullNameNL = \${random.name.fullName(nl)}</code>
<code>\${random.name.lastName()}</code>	Returns a last name.	<code>randomLastName = \${random.name.lastName()}</code>
<code>\${random.name.lastName(locale)}</code>	Returns a last name based on locale.	<code>randomLastNameNL = \${random.name.lastName(nl)}</code>
<code>\${random.name()}</code>	Returns a name.	<code>randomName = \${random.name()}</code>

<code>\${random.name(locale)}</code>	Returns a name based on locale.	<code>randomNameNL = \${random.name(n1)} }</code>
<code>\${random.name.nameWithMiddle()}</code>	Returns a name with middle name.	<code>randomNameWithMiddle = \${random.name.nameWithMiddle()}</code>
<code>\${random.name.nameWithMiddle(locale)}</code>	Returns a name with middle name based on locale.	<code>randomNameWithMiddleNL = \${random.name.nameWithMiddle(n1)}</code>
<code>\${random.name.title()}</code>	Returns a name title.	<code>randomTitle = \${random.name.title()}</code>
<code>\${random.name.title(locale)}</code>	Returns a name title based on locale.	<code>randomTitleNL = \${random.name.title(n1)}</code>
<code>\${random.name.username()}</code>	Returns a username.	<code>randomUsername = \${random.name.username()}</code>
<code>\${random.name.username(locale)}</code>	Returns a username based on locale.	<code>randomUsernameNL = \${random.name.username(n1)}</code>

FakerNumberFunctions

Function Name	Description	Example
---------------	-------------	---------

<code>\${random.number.digit()}</code>	Returns a digit from 0-9 inclusive.	<code>randomDigit = \${random.number.digit()}</code>
<code>\${random.number.digitNotZero()}</code>	Returns a digit from 1-9 inclusive.	<code>randomDigitNotZero = \${random.number.digitNotZero()}</code>
<code>\${random.number()}</code>	Returns a number.	<code>randomNumber = \${random.number()}</code>
<code>\${random.number(numberOfDigits)}</code>	Returns a number with length based on 'numberOfDigits'.	<code>randomNumberDigits = \${random.number(5)}</code>
<code>\${random.number.NonStrict(numberOfMaxDigits)}</code>	Returns a number with a max length based on 'numberOfMaxDigits'.	<code>randomNumberNonStrict = \${random.number.NonStrict(5)}</code>
<code>\${random.number.double(maxNumberOfDecimals, min, max)}</code>	Returns a double with decimals based on 'maxNumberOfDecimals' between given 'min' and 'max'.	<code>randomDouble = \${random.number.double(2, 1, 100)}</code>

Faker Code Functions

Function Name	Description	Example
<code>\${random.code.isbn10()}</code>	Returns an ISBN-10 code.	<code>\${random.code.isbn10()}</code>

<code>\${random.code.isbn10WithSeperators() }</code>	Returns an ISBN-10 code with separators (-).	<code>\${random.code.isbn10WithSeperators() }</code>
<code>\${random.code.isbn13() }</code>	Returns an ISBN-13 code.	<code>\${random.code.isbn13() }</code>
<code>\${random.code.isbn13WithSeperators() }</code>	Returns an ISBN-13 code with separators (-).	<code>\${random.code.isbn13WithSeperators() }</code>
<code>\${random.code.isbnGroup() }</code>	Returns an ISBN Group code.	<code>\${random.code.isbnGroup() }</code>
<code>\${random.code.isbnGs1() }</code>	Returns an ISBN GS1 code.	<code>\${random.code.isbnGs1() }</code>
<code>\${random.code.isbnRegistrant() }</code>	Returns an ISBN Registrant code.	<code>\${random.code.isbnRegistrant() }</code>

Faker Crypto Functions

Function Name	Description	Example
<code>\${random.crypto.md5() }</code>	Returns a random MD5 hash.	<code>\${random.crypto.md5() }</code>
<code>\${random.crypto.sha1() }</code>	Returns a random SHA-1 hash.	<code>\${random.crypto.sha1() }</code>
<code>\${random.crypto.sha256() }</code>	Returns a random SHA-256 hash.	<code>\${random.crypto.sha256() }</code>
<code>\${random.crypto.sha512() }</code>	Returns a random SHA-512 hash.	<code>\${random.crypto.sha512() }</code>

Faker Finance Functions

Function Name	Description	Example
<code>\${random.finance.iban()}</code>	Returns a random IBAN based on a random country code.	<code>\${random.finance.iban()}</code>
<code>\${random.finance.iban(countryCode)}</code>	Returns a random IBAN based on a specified country code.	<code>\${random.finance.iban("NL")}</code>
<code>\${random.finance.bic()}</code>	Returns a random BIC (Business Identifier Code).	<code>\${random.finance.bic()}</code>
<code>\${random.finance.creditCard()}</code>	Returns a random credit card number based on a random credit card type.	<code>\${random.finance.creditCard()}</code>
<code>\${random.finance.creditCard(creditCardType)}</code>	Returns a random credit card number based on the specified credit card type.	<code>\${random.finance.creditCard(VISA)}</code>
